Produkte
Mainboard Serie
»939A785GMH
»Überblick
»Spezifikationen
»Download
»Handbuch
»FAQ
»CPU Support Liste
»Speicher QVL

ASRock Channel on YouTube
facebook Follow ASRock on facebook now!
ASRock Forum
FORMULA
FATAL1TY Gaming Motherboard series
Windows 8, Wir sind bereit!
ASRock B75
2012 ASROCK INTEL series motherboard
OVERCLOCK KING
ASRock Tech Zone

939A785GMH

Translate

- Integrated AMD Radeon HD 4200 graphics, DX10.1 class iGPU, Shader Model 4.1, Max. shared memory 512MB
- Supports AMD Hybrid CrossFireX™
- Multi VGA Output options: D-Sub, DVI-D and HDMI
- Supports ASRock Instant Boot, Instant Flash, OC Tuner, Intelligent Energy Saver, OC DNA, APP Charger
- Free Bundle : CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suite

Dieses Modell wird nicht in allen Regionen der Welt verkauft. Bezüglich der Verfügbarkeit in Ihrer Region kontaktieren Sie bitte Ihren Händler.

Produkt Spezifikationen

Generelles	
CPU	- Socket 939 for AMD Athlon™ 64FX / 64X2 / 64 processors - Supports AMD's Cool 'n' Quiet Technology - FSB 1000 MHz (2.0 GT/s) - Supports Untied Overclocking Technology - Supports Hyper-Transport Technology
Chipsatz	- Northbridge: AMD 785G - Southbridge: AMD SB710
Arbeitsspeicher	- Dual Channel DDR memory technology - 4 x DDR DIMM slots - Supports DDR 400/333/266 non-ECC, un-buffered memory - Max. capacity of system memory: 4GB* *Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.
BIOS	- 8Mb AMI Legal BIOS - Supports "Plug and Play" - ACPI 1.1 Compliance Wake Up Events - Supports jumperfree - SMBIOS 2.3.1 Support - VCCM, NB Voltage Multi-adjustment
Audio, Video und Netzwerk	
Grafik	- Integrated AMD Radeon HD 4200 graphics - DX10.1 class iGPU, Shader Model 4.1 - Max. shared memory 512MB - Multi VGA Output options: D-Sub, DVI-D and HDMI - Supports HDMI Technology with max. resolution up to 1920x1200 (1080P) - Supports Dual-link DVI with max. resolution up to 2560x1600 @ 75Hz - Supports D-Sub with max. resolution up to 2048x1536 @ 60Hz - Supports HDCP function with DVI and HDMI ports - Supports Full HD 1080p Blu-ray (BD) / HD-DVD playback with DVI and HDMI ports
Audio	- 7.1 CH HD Audio (Realtek ALC888 Audio Codec)
LAN	- PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Realtek RTL8111DL - Supports Wake-On-LAN - Supports PXE
Erweiterungsslots/Konnektivität	
Steckplätze	- 1 x PCI Express 2.0 x16 slot (blue @ x16 mode) - 1 x PCI Express 2.0 x1 slot - 2 x PCI slots - Supports AMD Hybrid CrossFireX™
Anschluss	- 5 x SATA2 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 10 and JBOD), NCQ, AHCI and "Hot Plug" functions - 1 x ATA133 IDE connector (supports 2 x IDE devices) - 1 x Floppy connector - 1 x IR header - 1 x COM port header - 1 x Print port header - CPU/Chassis/Power FAN connector - 24 pin ATX power connector - 4 pin 12V power connector - CD in header - Front panel audio connector - 3 x USB 2.0 headers (support 6 USB 2.0 ports)
ATX-Blende	I/O Panel - 1 x PS/2 Keyboard Port - 1 x D-Sub Port - 1 x DVI-D Port - 1 x HDMI Port - 1 x Optical SPDIF Out Port - 4 x Ready-to-Use USB 2.0 Ports - 1 x eSATA2 Port - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED)

	- HD Audio Jack: Rear Speaker / Central / Bass / Line in / Front Speaker / Microphone
Sonstige Features/Verschiedenes	
Einzigartige Features	- ASRock OC Tuner - ASRock Intelligent Energy Saver - ASRock Instant Boot - ASRock Instant Flash - ASRock OC DNA - ASRock APP Charger - Hybrid Booster: - CPU Frequency Stepless Control - ASRock U-COP - Boot Failure Guard (B.F.G.)
Support-CD	- Drivers, Utilities, AntiVirus Software (Trial Version), CyberLink MediaEspresso 6.5 Trial, ASRock Software Suite (CyberLink DVD Suite - OEM and Trial; Creative Sound Blaster X-Fi MB - Trial; ASRock MAGIX Multimedia Suite - OEM)
Produktzubehör	- Quick Installation Guide, Support CD, I/O Shield - 2 x SATA Data Cables
Hardware überwachung	- CPU Temperature Sensing - Chassis Temperature Sensing - CPU/Chassis/Power Fan Tachometer - CPU Quiet Fan - Voltage Monitoring: +12V, +5V, +3.3V, Vcore
Formfaktor	- Micro ATX Form Factor: 9.6-in x 8.6-in, 24.4 cm x 21.8 cm - Solid Capacitor for CPU Power
Betriebssystem	- Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP Media Center / XP 64-bit compliant
Zertifizierungen	- FCC, CE, WHQL - ErP/EuP Ready (ErP/EuP ready power supply is required)

Achtung:
Bitte beachten Sie, dass Overclocking, inklusive dem Verändern von BIOS-Einstellungen und der Nutzung von Overclockingprogrammen von Drittherstellern, immer ein gewisses Risiko bürgt. Overclocking kann ihre Systemstabilität beeinflussen oder aber zu Schäden Ihrer Komponenten und Geräte führen. Die Ausführung geschieht auf eigene Gefahr und Kosten. Für Schäden die durch Overclocking verursachet werden sind wir nicht verantwortlich.

Die Spezifikationen können ohne vorherigen Hinweis geändert werden. Die Marken und Produktnamen sind Schutzmarken der jeweiligen Firmen. Alle Konfigurationen die von den original Spezifikationen abweichen werden nicht garantiert.

© 2002-2012 ASRock Inc Alle Rechte vorbehalten | Informationen die auf asrock.com veröffentlicht werden, können ohne Hinweis geändert werden.
Das oben abgebildete User-Interface ist ein Referenzbeispiel. Das tatsächliche User-Interface kann von der Abbildung abweichen.